



Shaft dia. mm	Unit number	Nominal dimensions mm								Bolt size mm	Bearing number	Housing number	Mass of unit Kg
		a	e	i	g	t	s	z	Bi				
20	UKF 205	95	70	16	13	27.0	12	35.5	35	M 10	UK 205	F 205	0.68
25	UKF 206	108	83	18	13	31.0	12	39.0	38	M 10	UK 206	F 206	0.98
30	UKF 207	117	92	19	15	34.0	14	42.5	43	M 12	UK 207	F 207	1.24
35	UKF 208	130	102	21	15	36.0	16	46.5	46	M 14	UK 208	F 208	1.61
40	UKF 209	137	105	22	16	38.0	16	48.5	50	M 14	UK 209	F 209	1.90
45	UKF 210	143	111	22	16	40.0	16	50.0	55	M 14	UK 210	F 210	2.14
50	UKF 211	162	130	25	18	43.0	19	54.5	59	M 16	UK 211	F 211	2.65
55	UKF 212	175	143	29	18	48.0	19	61.0	62	M 16	UK 212	F 212	3.07
60	UKF 213	187	149	30	22	50.0	19	64.0	65	M 16	UK 213	F 213	4.42

- Remark: 1) Regular production in "J" tolerance.
 2) Bearing unit with grease holes and grease groove.
 3) Bearing unit without stop pin.