



Shaft dia. mm inch	Unit number	Nominal dimensions									Bolt size mm inch	Bearing number	Housing number	Mass of unit Kg
		a	e	i	g	t	s	z	Bi	n				
25 1	UCF 305	108	80	16	13	29	16	39	38	15	M 14	UC 305	F 305	1.01
	UCF 305-16	4-1/4	3-5/32	5/8	3/64	1-9/64	5/8	1-17/32	1.4961	0.5906	1/2	UC 305-16		1.00
30 1-1/8 1-1/4	UCF 306	125	95	18	15	32	16	44	43	17	M 14	UC 306	F 306	1.53
	UCF 306-18	4-59/64	3-47/64	45/64	19/32	1-17/64	5/8	1-47/64	1.6929	0.6693	1/2	UC 306-18		1.55
	UCF 306-20											UC 306-20		1.51
35 1-1/4 1-3/8	UCF 307	135	100	20	16	36	19	49	48	19	M 16	UC 307	F 307	1.86
	UCF 307-20	5-5/16	3-15/16	25/32	5/8	1-27/64	3/4	1-59/64	1.8898	0.7480	5/8	UC 307-20		1.92
	UCF 307-22											UC 307-22		1.88
40 1-1/2	UCF 308	150	112	23	17	40	19	56	52	19	M 16	UC 308	F 308	2.65
	UCF 308-24	5-29/32	4-13/32	29/32	43/64	1-37/64	3/4	2-13/64	2.0472	0.7480	5/8	UC 308-24		2.69
45 1-5/8 1-3/4	UCF 309	160	125	25	18	44	19	60	57	22	M 16	UC 309	F 309	3.21
	UCF 309-26	6-19/64	4-59/64	63/64	45/64	1-47/64	3/4	2-23/64	2.2441	0.8661	5/8	UC 309-26		3.29
	UCF 309-28											UC 309-28		3.23
50 1-7/8	UCF 310	175	132	28	20	48	23	67	61	22	M 20	UC 310	F 310	4.32
	UCF 310-30	6-57/64	5-13/64	1-7/64	25/32	1-57/64	29/32	2-41/64	2.4016	0.8661	3/4	UC 310-30		4.41
55 2	UCF 311	185	140	30	20	52	23	71	66	25	M 20	UC 311	F 311	5.24
	UCF 311-32	7-9/32	5-3/64	1-3/16	25/32	2-1/16	29/32	2-51/64	2.5984	0.9843	3/4	UC 311-32		5.42
60 2-1/4	UCF 312	193	150	33	22	56	23	78	71	26	M 20	UC 312	F 312	6.40
	UCF 312-36	7-19/32	5-29/32	1-19/64	55/64	2-13/64	29/32	3-5/64	2.7953	1.0236	3/4	UC 312-36		6.45
65 2-1/2	UCF 313	208	166	33	22	58	23	78	75	30	M 20	UC 313	F 313	7.54
	UCF 313-40	8-3/16	6-17/32	1-19/64	55/64	2-9/32	29/32	3-5/64	2.9528	1.1811	3/4	UC 313-40		7.59
70 2-3/4	UCF 314	226	178	36	25	61	25	81	78	33	M 22	UC 314	F 314	9.02
	UCF 314-44	8-57/64	7-1/64	1-27/64	63/64	2-13/32	63/64	3-3/16	3.0709	1.2992	7/8	UC 314-44		9.03
75 3	UCF 315	236	184	39	25	66	25	89	82	32	M 22	UC 315	F 315	10.45
	UCF 315-48	9-19/64	7-1/4	1-17/32	63/64	2-19/32	63/64	3-1/2	3.2283	1.2598	7/8	UC 315-48		10.36
80 3-1/8	UCF 316	250	196	38	27	68	31	90	86	34	M 27	UC 316	F 316	14.00
	UCF 316-50	9-27/32	7-23/32	1-1/2	1-1/16	2-43/64	1-7/32	3-35/64	3.3858	1.3386	1	UC 316-50		14.03

Remark: 1) Regular production in "J" tolerance.
 2) Bearing unit with grease holes and grease groove.
 3) Bearing unit without stop pin.