



Shaft dia. mm	Unit number	Nominal dimensions mm											Bolt size mm	Bearing number	Housing number	Mass of unit Kg
		<i>a</i>	<i>p</i>	<i>e</i>	<i>i</i>	<i>s</i>	<i>j</i>	<i>k</i>	<i>g</i>	<i>f</i>	<i>z</i>	<i>Bi</i>				
20	UKFC 205	115	90	63.6	10	12	6	7	21.0	70	29.5	35	M 10	UK 205	FC 205	0.93
25	UKFC 206	125	100	70.7	10	12	8	8	23.0	80	31.0	38	M 10	UK 206	FC 206	1.18
30	UKFC 207	135	110	77.8	11	14	8	9	26.0	90	34.5	43	M 12	UK 207	FC 207	1.54
35	UKFC 208	145	120	84.8	11	14	10	9	26.0	100	36.5	46	M 12	UK 208	FC 208	1.85
40	UKFC 209	160	132	93.3	10	16	12	10	26.0	105	36.5	50	M 14	UK 209	FC 209	2.42
45	UKFC 210	165	138	97.6	10	16	12	14	28.0	110	38.0	55	M 14	UK 210	FC 210	2.64
50	UKFC 211	185	150	106.1	13	19	12	13	30.0	125	42.5	59	M 16	UK 211	FC 211	3.57
55	UKFC 212	195	160	113.1	17	19	12	15	36.0	135	49.0	62	M 16	UK 212	FC 212	4.53
60	UKFC 213	205	170	120.2	16	19	14	15	35.0	145	50.0	65	M 16	UK 213	FC 213	5.02

- Remark: 1) Regular production in "J" tolerance.
 2) Bearing unit with grease holes and grease groove.
 3) Bearing unit without stop pin.