


Shaft dia. mm	Bearing number	Nominal dimensions mm					Basic load ratings N		Weight Kg
		<i>d</i>	<i>D</i>	<i>Bi</i>	<i>C</i>	<i>F</i>	dynamic <i>Cr</i>	static <i>Cor</i>	
20	UK 205 D1	25	52	<u>23</u>	17	<u>4.3</u>	14,000	7,850	0.15
25	UK 206 D1	30	62	<u>26</u>	19	<u>4.7</u>	19,500	11,300	0.25
30	UK 207 D1	35	72	27	20	<u>4.6</u>	25,700	15,300	0.37
35	UK 208 D1	40	80	29	21	<u>4.6</u>	29,100	17,800	0.48
40	UK 209 D1	45	85	30	22	<u>4.9</u>	32,500	20,400	0.53
45	UK 210 D1	50	90	31	<u>24</u>	<u>5.5</u>	35,000	23,200	0.59
50	UK 211 D1	55	100	33	<u>25</u>	<u>5.4</u>	43,500	29,200	0.77
55	UK 212 D1	60	110	36	27	<u>5.9</u>	52,500	36,000	1.03
60	UK 213 D1	65	120	<u>38</u>	28	<u>5.5</u>	57,500	40,000	1.36

Remark: 1) Bearing with grease holes and grease groove.  
2) Bearing without stop pin.



**Technical supplement**

<b>Cages</b>	<b>Slinger</b>	<b>Precision</b>	<b>Grease</b>
Steel	Steel	Normal	Shell Alvania RLQ 2

Remark: If you have more inquiry of technical, please inquire **SLB** web-site: [Http://www.slbgroup.com](http://www.slbgroup.com).